

RIS

A non-clogging, component seal for tough slurry applications

The RIS seal has a unique, non-clogging design that does not utilize springs or bellows. The innovative design of the adaptive components allows the seal to be installed from the wet-end of the pump and to be adjusted externally. With many pump designs, the seal may be reset automatically during impeller clearance adjustment.



Features and Benefits

- The stationary seal face is attached to a smoothly contoured flexible rubber element which holds the seal faces together and absorbs relative shaft movement when the pump is in operation.
- A true non-clogging design provides longer MTBF with the rubber in shear component.
- External adjustments compensate for minor seal wear with no pump disassembly and compensate for pump misalignment.
- A lack of dynamic gaskets provides longer MTBF by eliminating seal face hang-ups.
- Extensive factory and field tests on hard slurries insures consistent and peak performance.
- With the control of slurry composition no flush is required, saving water and energy costs.
- Eliminating process leakage reduces water and disposal problems, packing sleeve wear and bearing failures.

Materials of Construction

Stationary Assembly CD-4MCu and Alloy C-276

Balance of Parts AISI 316, CE-4MCu and Alloy C-276

Other materials available optionally

Seal Faces Silicon Carbide or Tungsten Carbide

Elastomers Bortex I* Rubber in Shear Element
O-rings Ethylene-Propylene

*Bortex™ is a rubber compound developed by Flowserve

Operating Parameters

Maximum Static Pressure (for hydrotesting): 300 psig (2062 kPa) at Ambient Temperature


Minimum Seal Chamber Pressure (all sizes): 5 psig (35 kPa). If necessary, remove back vanes from impeller to avoid seal chamber pressures below 5 psig.

Tapered self-venting seal chamber recommended for proper product circulation and solids distribution. Recommended Tapered Angle "T": 10° min. to 30° max.

Water based slurries with maximum 5.0 MOH particle hardness (when using Tungsten Carbide Faces) and 7.0+ MOH particle hardness (when using Silicon Carbide Faces). Operates in pH levels from 2-14.


Shaft size: Up to 9-1/4 inches (234.7mm) covered by seven seal sizes.

Surface speed: up to 35 ft./sec. (11 m/sec.)



Dimensional Dimension inch (millimeters)

Seal Size	A	B	C	D	E
1875	1.750 (45)	2.940 (74.68)	2.522 (64.06)	2.562 (65.1)	1.935 (49.1)
2750	2.625 (67)	3.875 (98.43)	2.799 (71.09)	2.531 (64.3)	2.810 (71.4)
3750	3.635 (92)	4.875 (123.83)	2.799 (71.09)	2.531 (64.3)	3.810 (96.8)
4500	4.250 (108)	6.250 (158.25)	3.882 (98.60)	3.032 (77.0)	4.562 (116)
5500	5.250 (133)	7.250 (184.15)	4.006 (101.75)	3.032 (77.0)	5.562 (141)
6500	6.250 (159)	8.250 (209.55)	3.032 (108.13)	6.562 (77.0)	6.562 (167)
7500	7.250 (184)	9.250 (234.95)	4.381 (234.95)	3.032 (77.0)	7.562 (192)
9500	9.250 (235)	11.250 (285.75)	4.757 (120.83)	3.032 (77.0)	9.562 (243)



Typical Applications

Industry	Application	Seal Size	Press PSI (Bar)	Temp F (C)
Power, FGD	Recycle Limestone/Gypsum	4500-9500	30-50 (2-3.3)	120-150 [49-66]
Power	Thickener Underflow	1875-3750	30-75 (2-5)	Ambient
Power	Bottom Ash Removal	4500-5500	30-75 (2.5)	Ambient
Ore Processing	Reagent Feed	1875-3750	20-50 (1.3-3.3)	130-160 (54-71)
Phosphate Chemical	Phosphoric Acid/Gypsum	4500-7500	30-75 (2-5)	150-190 (66-88)
Alumina	Alumina Hydrate/Clarification	1875-7500	30-75 (2-5)	150-190 (66-88)
Iron Ore	Taconite Concentrate	4500-5500	20-75 (1.3-5)	Ambient

FSD151eng REV 03-07 Printed in USA

To find your local Flowserve representative and find out more about Flowserve Corporation visit www.flowserve.com

USA and Canada
Kalamazoo, Michigan USA
Telephone: 1 269 381 2650
Telefax: 1 269 382 8726

Europe, Middle East, Africa
Roosendaal, The Netherlands
Telephone: 31 165 581400
Telefax: 31 165 552622

Asia Pacific
Singapore
Telephone: 65 6544 6800
Telefax: 65 6214 0541

Latin America
Mexico City
Telephone: 52 55 5567 7170
Telefax: 52 55 5567 4224

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.