

DUCT DETECTORS

DESCRIPTION

The Fike P/N 63-028, -029, -030, -031, 67-029 and 67-030 duct detectors are the latest in analog and conventional (4-wire) duct detection. All models incorporate Fike NS sensor technology for advanced detection. The analog duct detector allows additional features such as user selectable alarm levels, pre-alarm, alarm verification and drift compensation.

SPECIFICATIONS/OPTIONS

All Models

- Include duct housing and detector
- Terminal blocks accept up to 14 AWG wire
- Form C relays rated 10A 115V
 Form A relay rated 1A 24V
- Compatible with sampling tubes:

Fike P/N 02-4630 (STS-2.5) 2.5 ft Fike P/N 02-4631 (STS-5.0) 5.0 ft Fike P/N 02-4632 (STS-10.0) 10.0 ft

Analog Models

- Operates on the Cheetah digital signal line circuit
- Uses NS analog photo detector
- Detector can be adjusted for alarm level sensitivities between 0.9 to 2.7%/ft obscuration
- Pre-alarm level can be set as low as 0.1%/ft obscuration
- Fike P/N 63-028 (DH-98-A) Base model
- Fike P/N 63-029 (DH-98-AR) Same as 63-028 except provides:
 - Remote alarm and remote pilot LED outputs
 - One Form C alarm relay
 - One Form C trouble relay
 - · Provides input for remote test switch
 - Requires separate 24Vdc power source

Conventional (4-wire) models

- Can be magnet tested without removing the housing cover
- Provides one each; Form C alarm relay, Form C trouble relay, and Form A alarm relay
- Provides outputs for alarm LED and pilot LED
- Provides input for remote test and remote reset switch
- Operates on 24Vdc or 24Vac. Additionally, each model has a 115Vac or 230Vac input
- Fike P/N 63-030 (DH-98-P) photo detector, 115Vac
- Fike P/N 63-031 (DH-98-HVP) photo detector, 230Vac
- Fike P/N 67-029 (DH-98-I) ion detector, 115Vac
- Fike P/N 67-030 (DH-98-HVI) ion detector, 230Vac

Form No. P.1.14.01-2

(This page is left blank intentionally)

