



Description & Features:

- Low pressure gauge kit in a protective plastic blow molded case
- Re-zero with external recalibration screw
- Plastic blow molded case for added durability
- Sleek design featuring secure latch
- Pump and fittings for simplified and quick connections
- ASME B40.100 compliant
- CRN registered
- 5 year warranty

Applications:

- Portable leak and loss of pressure detection unit for gas lines

Gauge Specifications

Dial	2.5" (63mm) white aluminum with black markings
Case/Ring	Steel, painted black with steel ring
Lens	Polycarbonate snap in
Connection	Rubber hand pump with hose and mini ball valve with handle and 1/2" NPTF x 1/4" NPTF test block and 1/2" NPTM x 1/2" NPTM nipple, 1/2" NPTF x 3/4" NPTM adapter and 3/4" NPTF x 1" NPTM adapter
Movement	Engineered plastic upper and lower plate with brass pinion and sector
Pointer	Aluminum, anodized black
Ambient Temperature	-40°F to 150°F (-40°C to 65°C)
Accuracy	±3-2-3% ANSI/ASME Grade B
Enclosure Rating	IP52
Case	Plastic blow molded (11.875" x 18")

Case and Accessory Specifications

Hand Pump and Hose	10" rubber hose with hand pump
Mini Ball Valve	SMV series valve with forged brass body 1/4" NPTF x 1/4" NPTM
Test Block	Chrome plated steel
Accessories	Pressure fitting with easy to install clamp
Nipple	Carbon steel 1/2" NPTM
Fittings	Carbon steel 1/2" NPTF x 3/4" NPTM and 3/4" NPTF x 1" NPTM

Order Codes (products in bold are normally stock in North America)

Pressure Range	Code
0/5 psi	PLPT0005