



Description & Features:

- Rugged, 2" (50mm) forged brass case and connection
- Forged brass case and socket
- Glycerin filled
- 3/8" Steck-O connection
- 3 coloured zone dial for easier pressure reading
- 0-9,000 psi/bar
- ASME B40.100 compliant
- CRN registered
- 5 year warranty

Applications:

- Hydraulic shoring commonly used in long wall mining

Specifications

Dial	2" (50mm): White aluminum, black lettering, triple colour scale (red, green, yellow)
Case	One-piece forged brass case
Wetted Parts	Brass
Fill Liquid	Glycerin standard
Lens	Polycarbonate
Connection	3/8" Steck-O connection, quick connect with 90 Durometer Buna N sealing o-ring and PTFE washer (bottom connection)
Pointer	Aluminum, anodized black
Over-pressure Limit	25% of full scale value
Working Pressure	Maximum 70% of full scale value
Ambient/Process Temperature	-40°F to 150°F (-40°C to 65°C) dry -4°F to 150°F (-20°C to 65°C) glycerin-filled
Accuracy	±3-2-3% ANSI/ASME Grade B
Enclosure Rating	IP65

Order Codes (products in bold are normally in stock)

Pressure Range	Code
0/9,000 psi/bar	PMN306

Other ranges and connection sizes available upon request. For scale change, refer to How to Order Guide for scale codes.

