



### Description & Features:

- Low and high pressure gauge kit in a protective plastic blow molded case
- Re-zero with external recalibration screw
- Plastic blow molded case for added durability
- Sleek design featuring secure latch
- Pump and fitting for simplified and quick connections
- ASME B40.100 compliant
- CRN registered
- 5 year warranty

### Applications:

- Portable leak and loss of pressure detection unit for gas and water lines

Specifications	Gas Test Gauge (1)	Water Test Gauge (2)
<b>Dial</b>	2.5" (63mm) white aluminum with black markings	2" (50mm) white aluminum with black markings
<b>Case/Ring</b>	Steel, painted black with steel ring	Steel, painted black
<b>Lens</b>	Polycarbonate snap in	Polycarbonate
<b>Connection</b>	Rubber hand pump with hose and mini ball valve with handle and 1/2" NPTF x 1/4" NPTF test block and 1/2" NPTM x 1/2" NPTM nipple	3/4" NPTF x M8x0.8 test block with cap
<b>Pressure Range</b>	0/5 psi	0/160 psi
<b>Movement</b>	Engineered plastic upper and lower plate with brass pinion and sector	Brass
<b>Pointer</b>	Aluminum, anodized black	Aluminum, black
<b>Ambient Temperature</b>	-40°F to 150°F (-40°C to 65°C)	-40°F to 150°F (-40°C to 65°C)
<b>Accuracy</b>	±3-2-3% ANSI/ASME Grade B	±3-2-3% ANSI/ASME Grade B
<b>Enclosure Rating</b>	IP52	IP52
<b>Case</b>	Plastic blow molded (11.875" x 18")	

**Order Codes (products in bold are normally stock in North America)**

Kit	Additional Hand Pump
PGWT0100	PHPT0100